

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
5 April 2001 (05.04.2001)

PCT

(10) International Publication Number  
**WO 01/23008 A1**

(51) International Patent Classification<sup>7</sup>: A61L 9/12

(21) International Application Number: PCT/EP00/07489

(22) International Filing Date: 2 August 2000 (02.08.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
99810876.5 29 September 1999 (29.09.1999) EP

(71) Applicant (for all designated States except US): GIVAUDAN SA [CH/CH]; Chemin de la Parfumerie 5, CH-1214 Vernier (CH).

(72) Inventors; and

(75) Inventors/Applicants (for US only): HART, Gerald,

Leslie [GB/GB]; 38 Villiers Avenue, Surbiton, Surrey KT5 8BD (GB). NAISH, Guy, Edward [GB/GB]; 44 Alexandra Street, Narborough, Leicester LE9 5DD (GB). GOHIL, Kishen [GB/GB]; 21 Consfield Avenue, New Malden, Surrey KT3 6HB (GB).


(74) Agent: SCHAAD, BALASS, MENZL; Dufourstrasse 101, Postfach, CH-8034 Zürich (CH).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European

[Continued on next page]

(54) Title: UNIT FOR THE TRANSFER AND DISTRIBUTION OF A LIQUID



(57) Abstract: A unit (1) for the transfer and distribution of the liquid (27) using capillary action has an elongated shaft (2) and a screen (3). The shaft (2) includes a first capillary medium (4) suitable for drawing the liquid (27) from a reservoir (26) into the shaft (2) when a bottom portion (20) of the shaft (2) is disposed in the liquid. The screen (3) is connected to the shaft (2) and includes a second capillary medium (5) suitable for receiving the liquid (27) drawn by the first capillary medium (4) and distributing it over at least a major part of the screen (3) where it evaporates.

WO 01/23008 A1



patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *With international search report.*

## Unit for the transfer and distribution of a liquid

The present invention relates to a unit for the transfer and distribution of a liquid and a method of manufacturing the same according to claims 1 respectively 12. The  
5 invention further relates to a refill for a dispenser for volatile liquids according to claim 16.

### BACKGROUND OF THE INVENTION

In order to transfer liquids it is known to use capillary  
10 action which is dependent on the cohesive forces within the liquid and the adhesive forces of the liquid to a capillary medium comprising small channels, e.g. pores or spaces between fibers. Such a capillary medium, e.g. a wick, being introduced through an opening into a  
15 reservoir, can therefore be used to draw a liquid out of said reservoir passively by means of capillary action only, i.e. without additional sucking. The transferred liquid may be used to distribute chemical substances to the ambient air in order to generate or mask an odour, to  
20 evoke a medical or organoleptic effect or to affect insects.

The US 5 114 625 discloses a fragrance dispenser with a liquid reservoir and a wick with a liquid receiving end disposed in the reservoir for drawing liquid therefrom  
25 into the wick. A portion of the wick length is exposed to an air flow provided by a fan.

However, the distribution of volatile chemical substances contained in the liquid in the air flow is not

- 2 -

sufficiently homogenous when the air flow is brushing over the wick. Further, in most cases dispensing a substance cannot be done without generation of an external air flow in order to evaporate a given amount of liquid per unit  
5 time.

The wicks used in prior art dispensing devices are difficult to exchange as they have to be mounted in such a way that the wick is arranged in a defined position relative to the reservoir. This is rendered difficult as  
10 wicks are generally soft. Further, the reservoir including the wick has to be tight to prevent spilling of the liquid and uncontrolled evaporation. The same problem arises with a refill for such a device. A refill already including a wick has to be tightly sealed before use, while refill and  
15 wick separated from each other have to be such that the wick is easy and clean to insert and the refill is tight before and during use.

It is therefore an object of the invention to provide a unit for the transfer and distribution of a volatile  
20 liquid that has a good efficiency in evaporating liquid, is easy and cheap to manufacture and is easily and hygienically insertable into a reservoir, especially the reservoir of a refill.

It is another object of the invention to provide a method  
25 of manufacturing such an improved transfer unit.

It is a further object of the invention to provide a refill suited for the use with such a transfer unit.

SUMMARY OF THE INVENTION

- 3 -

The above and other objects of the invention are achieved by a transfer unit as specified in claim 1, a method of manufacturing the same as specified in claim 12, a refill as specified in claim 16 and a dispenser with such a transfer unit and such a refill.

According to the invention a shaft comprising a first capillary medium to draw a liquid into the shaft due to capillary action, e.g. a wick, scribe rod or a porous rod, is provided with an integrated screen to serve as an enlarged liquid receiving area from which the liquid is easily evaporated to the ambient air. To provide an enlarged area, the screen is preferably at least two to three times as wide as the shaft. By capillary action the liquid is drawn from the shaft to the screen and distributed over it, using a second capillary medium connected to the first capillary medium. As first capillary medium in general any material capable of absorbing and transferring a liquid due to capillary action is suited, e.g. material containing natural or synthetic fibers, woven or non-woven fabrics, porous media, capillary tubes, or a rod with external grooves, e.g. as described in US 4 913 350. As second capillary medium a material with open pores from which liquid evaporates is suited, e.g. material containing natural or synthetic fibers, woven or non-woven fabrics, porous media. In a preferred embodiment first and second capillary medium are a single piece, for example shaft and screen are made of a sheet of card board or non-woven welded or laminated material, which is cheap and therefore suited for the production of a mass article. Shaft and screen are preferably rigid to maintain the shape of the transfer unit and its position with respect to the reservoir when introduced into the dispenser.

- 4 -

In a preferred embodiment of the invention the screen is permeable to air flow through the screen in a direction approximately normal to the plane of the screen. This can be achieved by a screen having one or more openings. In one preferred embodiment there are a plurality of „small” openings, each with an area less than 5% of the total screen area, distributed preferably uniformly over the screen and result in openings in the screen totalling no more than 95%. By the screen material itself being capillary at least between the openings the liquid is distributed over the screen and around the openings where it evaporates. Additionally or alternatively, the openings or the whole screen area can be covered with another air permeable capillary medium, such as a gauze sheet or tissue paper, which additionally respectively solely receives and distributes the liquid. In this case there is not need for the openings being „small”, i.e. one or more „bigger” openings each with an area of equal to or greater than 5% of the total screen area can be used to transmit the air. To enhance evaporation, an externally generated air flow is advantageous but not essential.

The refill according to the invention comprises a reservoir containing the liquid, an outlet opening and a shaft receiving passage starting at the outlet opening and projecting inward. The shaft receiving passage is suitable for receiving the shaft of the transfer unit as described above. Preferably the receiving passage is dimensioned to tightly embrace the shaft, as this stabilizes the transfer unit and a capillary effect can be achieved between the shaft and the walls of the receiving passage enhancing the capillary action of the shaft itself. Another embodiment of the shaft may be envisaged where lower capillary action is required. This can be achieved through tapering of the

- 5 -

shaft for the lower portion of its length, such that it is not in intimate contact with the lower portion of the receiving passage. The refill and the shaft receiving passage may be moulded in one piece which can be produced at low cost. In a preferred embodiment the shaft receiving passage comprises a seal, e.g. a metal foil, plastic moulding, or any impervious material that can be easily punctured isolating the liquid in the reservoir from the outside. Preferably, the seal is located at the bottom end of the passage and may be punctured by the shaft when fully introduced into the refill. A commercial embodiment of this could have the shaft partially introduced into the shaft receiving passage and the action of inserting the refill into the main unit causes the shaft to break the seal. To facilitate breaking the seal the shaft preferably comprises a cutting member at its bottom portion, e.g. a tip or a thorn or a knife-like element. Seal location at the bottom end of the passage is advantageous as the narrow passage protects the seal against accidental damage. The refill can thus be sold ready for use without an extra cover of the outlet opening, such as a lid, thus saving material, waste and manufacturing costs. Introduction of the shaft can be accomplished without spilling.

The transfer unit is preferably sold in a blister package containing one or more transfer units or a refill and an isolated unit insertable into the refill.

A coating of the lateral shaft faces respectively a layer around these faces impermeable to liquid is advantageous as it prevents softening of the shaft and stabilizes the shaft. Further, it enables the control of the dispensed amount as liquid flow can be stopped by tilting or turning

- 6 -

the reservoir, thus preventing contact of the bottom portion with the liquid.

#### BRIEF DESCRIPTION OF THE DRAWINGS

- Fig. 1 shows a transfer unit with a shaft and a screen with a plurality of „small“ openings;
- Fig. 2 shows a transfer unit with a shaft and a screen both having a plurality of „small“ openings;
- Fig. 3 shows a transfer unit with a shaft and a screen having one „big“ opening;
- Fig. 3A shows a generic shaft which may have screens as depicted in Fig. 1 - 3, but has tapered lower portion;
- Fig. 4a-c shows different views of a shaft receiving passage;
- Fig. 5a,b shows the insertion of a transfer unit into the shaft receiving passage of fig. 4a-c;
- Fig. 5c,d shows a view of a shaft receiving passage with the tapered shaft as shown on Fig. 3A
- Fig. 6a,b shows a refill with a transfer unit;
- Fig. 7 shows one method of manufacturing the transfer units as shown in fig. 1;
- Fig. 8a shows an example of a perforated sheet as a sheet material for transfer units as shown in fig. 2;



- 7 -

Fig. 8b shows a method of manufacturing transfer units as shown in fig. 2 using the sheet of fig. 8a;

Fig. 9a,b shows a method of manufacturing transfer units as shown in fig. 3.

5

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 shows a transfer unit 1 with an elongated shaft 2 and a screen 3. The shaft 2 consists of a first capillary medium 4, here absorbent card board 4', preferably 1 to 4 mm thick. The shaft 2 may have, but is not restricted to a rectangular shape with a width W1 of preferably 5 to 10 mm. The length of the shaft 2 is greater than the width W1 and is chosen such that at least the bottom portion 20 of the shaft 2 is in contact with the liquid, e.g. a perfume, when introduced into a liquid reservoir. The bottom portion 20 has a tip 20' to facilitate breaking a seal, as shown in fig. 5a,b. The screen 3 consists of a second capillary medium 5 with a plurality of „small“ openings 6 punched out to allow air to pass through, each opening 6 covering less than 5% of the total screen area. The width W2 of the circular screen 3 is about three times the width W1 of the shaft 2. Screen 3 and shaft 2 are made of the same material, a card sheet, i.e. in this embodiment for the second capillary medium 5 the same material as for the first capillary medium 4 is used. Alternatively, different capillary materials could be connected to enable liquid transfer to the screen 3.

Fig. 2 shows another example for a transfer unit 7 with a shaft 8 and a screen 9 both having a plurality of „small“ openings 12, 12'. Its shape is generally the same as of

- 8 -

the unit of fig. 1. As a capillary material for the capillary media 11 and 10 of screen 9 respectively shaft 8 an absorbent card 10' with perforations that constitute the openings 12, 12' is used, e.g. as shown in Fig. 8a.

5 Fig. 3 shows a third example for a transfer unit 13 with a shaft 14 and a screen 15. The screen 15 comprises an annular frame 18 with a central opening 17, that covers approximately 80% of the screen area („big" opening). The opening 17 is covered with a sheet of capillary air  
10 permeable material, here a gauze sheet 19'. The gauze sheet 19' receives as a second capillary medium 19 liquid drawn into the shaft 14 and to the screen 15 by the first capillary medium 16. The frame 18 is made of the same material as the shaft 14, here card board 16, i.e. the  
15 frame contributes to the distribution and transfer of the liquid to the gauze sheet 19' using capillary action. Fig. 3A shows a transfer unit 1' with an elongated shaft 2' and a screen 3. The shaft 2' consists of a first capillary medium 4' preferably 1 to 4 mm thick. The shaft 2' has a  
20 rectangular shape at its upper most portion directly below the screen, and a triangular taper for the remainder of its length with the taper comprising of 5% to 95% of the total length of the shaft. The length of shaft 2' is greater than the maximum width and is chosen such that at  
25 least the bottom portion of the shaft is in contact with the liquid

In another embodiment (not shown) the frame 18 is made of a non capillary material, such as plastic or metal, serving to stabilise the second capillary medium 19 which  
30 is connected to the shaft for liquid transfer. In yet another embodiment (not shown) the shaft itself comprises a frame made of non capillary material stabilising a first

- 9 -

capillary medium, e.g. a gauze sheet or a tissue paper, being connected to the second capillary medium, preferably the second capillary medium being an integral part of the first capillary medium.

5 Fig. 4a-c shows different views of a shaft receiving passage 21 dimensioned to receive the shaft of a transfer unit. A transfer unit 1 being introduced into the receiving passage 21 is shown in Fig. 5a,b. The receiving passage 21 may be an integral part of a refill for an air  
10 freshener or the like, as shown in fig. 6a, b, or may be suited for insertion into the outlet opening of a liquid reservoir.

The receiving passage 21 comprises an elongated sleeve 23 having a rectangular cross section dimensioned to tightly  
15 embrace the shaft 4 of transfer unit 1. The receiving passage 21 further comprises a fitting 22 adjacent to the sleeve 23 having circular cross section. The fitting is dimensioned to tightly fit into a circular outlet opening of a liquid reservoir 26. The fitting 22 comprises an  
20 annular flange 35 to seal the outlet opening when the passage 21 is inserted. In case the receiving passage is an integral part of the liquid reservoir 26 the fitting 22 is not essential as the passage 21 and the reservoir 26 can be moulded in one piece. The passage 21 guides the  
25 transfer unit 1 into a defined position with respect to the dispensing device, e.g. to a fan generating an air flow. In this position transfer unit 1 is mechanically stabilised by passage 21.

Fig. 5c-d are similar to Fig. 4b-c except that they depict  
30 a shaft receiving passage 23' containing a tapered shaft 2', as shown in Fig. 3a. The receiving passage has a cross

- 10 -

section dimensioned as not to tightly embrace the shaft 2' hence leaving a gap between the shaft and receiving passage of at least 1mm on both front and back sides. In this embodiment there will be a tight fitting portion at the top 36' of the receiving passage 23' to hold the transfer unit 9' in place.

The bottom opening of the passage 21 is closed with a foil seal 24 that can be punctured by the shaft 4 as shown in fig. 5b and 6b. The seal 24 isolates the liquid 27 contained in the reservoir 26 of the refill 25 from the outside, no extra lid is needed. When the transfer unit 1 is inserted, the tip 20' of its bottom portion 20 breaks the seal 24, the liquid 27 has access to the shaft 4 immediately, is drawn up to the screen 3 and evaporated.

Fig. 7, 8b and 9a-c show methods of manufacturing the transfer units as shown in Fig. 1 to 3. The transfer unit of fig. 1 is manufactured by punching a shape 29 with a circular main body 29', forming the screen afterwards, and an elongated part 29'', forming the shaft, from a sheet 28 of capillary material. This shape 29 can be punched in one go with a plurality of holes 29''' arranged within the main body shape 29' or before or after punching the holes 29'''.

A pre-perforated sheet or mat 30 of capillary material with a plurality of holes 31 as shown in fig. 8a serves as basis for manufacturing transfer units shown in fig. 2. A shape 29 as described above is punched from the sheet 30. The cut out shape is ready to use as a transfer unit.

The steps of an alternative manufacturing method are depicted in fig. 9a-c, where „big” holes 33 are punched from a continual mat or sheet 32 (fig. 9a). Then a strip

- 11 -

of continual air permeable capillary material 34 such as gauze is glued over the holes 33 (fig. 9b). A shape 29 as described above is punched from the sheet 32, where the shape 29 is positioned such that each hole 33 is located  
5 in the center of the circular main body 29'.

The inventive transfer units 1, 7, 13 as shown above can thus be manufactured at very low cost as the materials used, e.g. gauze, cardboard, fleece, are cheap and the methods of manufacturing described in fig. 7 to 9 involve  
10 three steps at most.

**Claims**

1. A unit (1, 1', 7, 13) for the transfer and distribution of a liquid (27) using capillary action with an elongated shaft (2, 2', 8, 14) including a  
5 first capillary medium (4, 10, 16) suitable for drawing the liquid (27) from a reservoir (26) and with a screen (3, 9, 35) including a second capillary medium (5, 11, 19) suitable for receiving the liquid (27) from the first capillary medium (4, 10, 16) and  
10 distributing it over at least a part of the screen (3, 9, 35) for evaporation.
2. Transfer unit (1, 1', 7, 13) according to claim 1, wherein the screen (3, 9, 35) is permeable to an air flow in a direction approximately normal to the plane  
15 of the screen (3, 9, 35).
3. Transfer unit (1, 1', 7, 13) according to claim 1 or 2, wherein the screen (3, 9, 35) comprises a planar frame (18) with at least one opening (6, 12, 17), the second capillary medium (5, 11, 19) being attached to  
20 the frame (18) covering the at least one opening (6, 12, 17).
4. Transfer unit (1, 1', 7, 13) according to claim 3, wherein the second capillary medium (5, 11, 19) comprises a sheet (19', 34) of air permeable  
25 material, preferably a thin woven or non-woven fabric, preferably gauze or tissue paper.
5. Transfer unit (1, 1', 7, 13) according to one of the preceding claims, wherein the screen (3, 9, 35) is at least partially made of a capillary material,

- 13 -

preferably a cellulose structure such as card (4', 10', 16') or a non-woven fleece material, and has a plurality of openings (6, 12, 17) through which air can be blown.

- 5    6.    Transfer unit (1, 1', 7, 13) according to one of the preceding claims, wherein the shaft (2, 2', 8, 14) is at least partially made of a capillary material, preferably a cellulose structure such as card (4', 10', 16') or a non-woven fleece material.
- 10   7.    Transfer unit (1, 1', 7, 13) according to one of the preceding claims, wherein the surface of the shaft (2, 8, 14) is permeable to liquid (27) at a bottom portion (20) and impermeable at other portions of the shaft (2, 8, 14).
- 15   8.    Transfer unit (1, 1', 7, 13) according to claim 7, wherein the shaft (2, 2', 8, 14) further comprises a layer, preferably a coating, covering the lateral surfaces of the shaft (2, 2', 8, 14), which is impermeable to liquid.
- 20   9.    Transfer unit (1, 1', 7, 13) according to one of the preceding claims, wherein the screen width (W2) is at least twice the shaft width (W1), preferably three times wider.
- 25   10.   Transfer unit (1, 1', 7, 13) according to one of the preceding claims, wherein the screen (3, 9, 35) and the shaft (2, 2', 8, 14) are made in one piece.
11.   Transfer unit (1, 1', 7, 13) according to one of the preceding claims, wherein the bottom part (20) of the shaft (2, 2', 8, 14) has cutting means (20') to

- 14 -

facilitate breaking or cutting a seal (24) in a shaft receiving passage (21) of a refill unit (25) for fragrance dispensers.


12. Method of manufacturing a unit (1, 1', 7, 13)  
5 according to one of the preceding claims, comprising the step of cutting at least one shape (29, 29', 29'') of an elongated shaft (2, 2', 8, 14) with an attached screen (3, 9, 35) wider than the shaft (2, 2', 8, 14) from a sheet material (28, 30, 32).
- 10 13. Method according to claim 12, wherein the basis sheet (28, 30, 32) consists of a capillary material, preferably card or a rigid fleece material, or comprises a capillary material, preferably a gauze sheet or tissue paper attached to and covering the  
15 sheet material (28, 30, 32).
14. Method according to claim 12, further comprising the step of cutting, preferably punching out at least one opening at least in those areas of the sheet material (28, 30, 32) where the screen shape (29') is located.
- 20 15. Method according to claim 14, further comprising the step of attaching at least one sheet of thin air permeable capillary material (34), preferably gauze or tissue paper, to the sheet material (28, 30, 32) after cutting the at least one opening (33).
- 25 16. Refill (25) for a dispenser for volatile liquids (27) comprising a reservoir (26) containing the liquid (27), an outlet opening (36) and a shaft receiving passage (21) extending from the outlet opening (36) inward suitable for receiving the shaft (2, 2', 8,




- 15 -

14) of the transfer unit (1, 7, 13) as claimed in one of the claims 1 to 11.


17. Refill (25) according to claim 16, wherein, when the shaft (2, 8, 14) is introduced into the shaft receiving passage (21), the bottom portion of shaft (2, 8, 14) is in contact with the liquid (27) and the screen (3, 9, 35) extends above the refill (25) and is exposable to an air flow.
18. Refill (25) according to claim 16 or 17, wherein the shaft receiving passage (21) comprises a sleeve (23) dimensioned to receive a shaft (2, 2', 8, 14) and made of a material impermeable to the liquid (27).
19. Refill according to claim 18, wherein the sleeve (2, 2', 8, 14) is dimensioned to tightly embrace the shaft (2, 2', 8, 14) down to or close to its bottom portion (20).
20. Refill according to one of the claims 16 to 19, wherein the shaft receiving passage (21) comprises a seal (24) isolating the liquid (27) in the reservoir (26) from the outlet opening, preferably located at the bottom end of the passage (21).
21. A dispenser comprising a refill (25) according to one of the claims 16 to 20 and a transfer unit (1, 1', 7, 13) according to one of the claims 1 to 11.




**Fig.1**




**Fig.2**




**Fig.3**




**Fig.3a**




**Fig.4a**



**Fig.4b**



**Fig.4c**

**Fig.5a****Fig.5b**




Fig.5c




Fig.5d




Fig. 6a




Fig. 6b





Fig.7

**Fig. 8a**






Fig.8b




Fig.9a




Fig.9b




Fig.9c

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 00/07489

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 A61L9/12

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 A61L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 725 152 A (AKYU MUNEKI) 10 March 1998 (1998-03-10) column 1, line 48 - line 58 claims 1,2	1-21
A	US 4 915 301 A (MUNTEANU MARINA A) 10 April 1990 (1990-04-10) column 2, line 22 - line 59 figure 1	1-21
A	DE 41 40 127 C (DRAGOCO GERBERDING & CO GMBH) 3 December 1992 (1992-12-03) the whole document	1-21
A	US 4 419 326 A (SANTINI THOMAS F) 6 December 1983 (1983-12-06) column 4, line 54 -column 5, line 23 figure 1	1-21

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \* & \* document member of the same patent family

Date of the actual completion of the international search

6 December 2000

Date of mailing of the international search report

14/12/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Heck, G

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 00/07489

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5725152 A	10-03-1998	JP 3088277 B JP 9117497 A	18-09-2000 06-05-1997
US 4915301 A	10-04-1990	CA 2002882 A,C GB 2224657 A,B	15-05-1990 16-05-1990
DE 4140127 C	03-12-1992	NONE	
US 4419326 A	06-12-1983	US 4413779 A CA 1197770 A	08-11-1983 10-12-1985